

Installation instructions

ENHANCE YOUR HOME & BUSINESS SECURITY



NOTE: Your Shutter Guard should be fitted to a solid concrete surface.

We recommend a minimum of 100mm thickness.

To fit your Shutter Guard, you will need the following tools:

- Power/hammer Drill
- 14mm Masonry Drill Bit
- 10.5mm hss drill bit
- 17mm spanner or socket set
- 13mm spanner or socket set
- Marker Pen

www.burtonsafes.co.uk

Brockholes Business Park, Rock Mill Road, Holmfirth, HD9 7BN




Product Contents


- Shutter Guard Floor Anchor Plate
- 2 Padlock Mounting Plate
- 3 Option C Mounting Plate
- 4 Option A Mounting Plate
- 5 Padlock
- 6 Ground Bolts
- 7 Coach Bolts M10 x 65
- 8 Coach Bolts M10 x 40
- 9 Washers M10
- 10 Nuts M10

Option A

Option B



Option C



FIXING INSTRUCTIONS

STEP 1

Choose which ilustration from the diagram below best suits your shuter layout

STEP 2

Hold the shutter mounting plate in position against the shutter, making sure the hinged anchor plate can fold over it leaving clearance for the padlock.

STEP 3

Mark the two holes on to the shutter using a marker pen

STEP 4

Using the 10.5mm drill bit, drill the holes in the shutter

STEP 5

Using the fixings provided, fix the shutter mounting plate in place on the shutter. Tighten with a 17mm spanner or socket set

STEP 6

Place the hinged anchor plate on the floor, making sure the hinge plate can go over the shutter plate lug. Mark the four holes on the floor using a marker pen.

STEP 7

Using a 14mm drill bit drill the 4 holes to a depth of 75mm. Clean the dust from the holes

STEP 8

Unscrew the shields from the fixings, insert the fixing through the anchor base plate and screw the shields back on to the fixing until the shield is nearly touching the underside of the anchor plate

STEP 9

Lower the shields into the drilled holes and gently tap down until it sits flush with the concrete floor





ENHANCE YOUR HOME & BUSINESS SECURITY

















Product Contents

- 1 Shutter Guard Floor Anchor Plate (X1)
- 2 Padlock Mounting Plate (X1)
- 3 Option C Mounting Plate (X1)
- 4 Option A Mounting Plate (X1)
- 5 Padlock (X1)

- 6 Ground Bolts (X4)
- 7 Coach Bolts M10 x 65 (X2)
- 8 Coach Bolts M10 x 40 (X2)
- 9 Washers M10 (X4)
- 10 Nuts M10 (X4)



