



burtonsafes.co.uk



LOCKING INSTRUCTIONS

DUAL LOCKING



LOCKING INSTRUCTIONS

DUAL LOCKING

ABOUT THE LOCK

For enhanced security your safe is fitted with two locks. To open your safe you will need to input a 6-digit code into the keypad of each lock. The bottom lock must be unlocked first, this is the keypad with the black plastic ring surrounding it. This keypad can be turned while the other keypad will remain stationary.

How to open the safe

- On the bottom keypad, enter a valid 6-digit code (the factory default is '123456')
- If the code has been entered correctly the lock will beep twice
- Turn the keypad clockwise until it stops
- Now on the top keypad, enter a valid 6-digit code (the factory default is '123456')
- If the code has been entered correctly the lock will beep twice
- Within 3 seconds, turn the safe handle
- Open the safe door

USER INSTRUCTIONS FOR EITHER LOCK

Incorrect Entry

- If an incorrect code has been entered, it will be followed by a long beep
- After 4 incorrect entries, a penalty time of 5 minutes will begin - during this time, no other code entries can be made
- When the penalty time is over enter a valid 6-digit code

NOTE: 2 more consecutive invalid codes will restart an additional 5 minutes penalty time

How to close the safe

- Ensure that the bolts are fully retracted (If necessary rotate the handle clockwise to retract the bolts)
- Gently push the door shut. Always ensure that there is nothing in the way of the closing door
- Turn the handle anti-clockwise until the stop position is reached
- Rotate the bottom keypad into the upright position. **N.B. Your safe will not be fully locked or insured if this step is missed!**

Activating the secondary code

(Using the master code)

- Press and hold key [1] until the lock beeps twice
- Enter the 6-digit MASTER code (This is your primary user code)
- Now enter a 6-digit code for the SECONDARY code; the lock will beep twice
- Enter the 6-digit code for the secondary code again to confirm. The lock will beep twice and the code is set.

Deleting the secondary code (Using the master code)

- Press and hold key [3] until the lock beeps twice
- Enter the 6-digit master code (Your primary user code)
- The secondary code is now deleted

Changing your code

- Unlock and open the safe door
- Press and hold key [0] until the lock beeps twice
- Enter the current 6-digit code of the user you wish to change (master or secondary) the lock will beep twice
- Now enter the new 6-digit code, the lock will beep twice
- Enter the new 6-digit code again to confirm; the lock will beep twice
- The code has now been changed for that user

NOTE: If there are any code entry errors, they will be followed by a long beep. The old code will remain valid and you can repeat the steps.

Programming the time delay and open window

A time delay is the time you have to wait between the entry of your code and the opening of your safe. An open window is the amount of time you have to open your safe. For example, if you wanted a 30 minute time delay and a 10 minute open window, this would mean that once you have entered a valid 6-digit code, you have to wait 30 minutes before you can open the safe door. After 30 minutes you will have 10 minutes to open the safe door. If you wait longer than 10 minutes, you have to start the process again.

- Press and hold key [9] until the lock beeps twice
- Enter the 6-digit master code
- Now enter the desired time delay and open window length, i.e. for a 30 minute time delay and 10 minute open window, enter: 3010
- The lock will beep twice
- Enter the time delay and open window again to confirm
- The lock will beep twice. The time delay and open window are now set

How to open the safe with the time delay active

- Enter a valid 6-digit code. If the code is entered correctly, the lock will beep twice
- When the time delay begins, the LED will flash every 2 seconds
- Once the time delay ends the open window will begin. During the open window, the lock will beep once every 2 seconds
- Input your user code a second time
- During this time, turn the handle to the open position and open the safe door

N.B. If this function is programmed on the bottom lock, turn the keypad before turning the safe handle)

How to change / remove the time delay active

- Enter a valid 6-digit code, if the code is entered correctly the lock will beep twice
- When the time delay begins the LED will flash every 2 seconds
- Once the time delay ends the open window will begin
- During the open window, follow the steps of programming the time delay to change time length
- To remove the time delay, you need to enter 0001 as the time delay and open window length

Current supply / battery change

- A series of beeps indicates that the battery is weak and must be replaced. Only use a 9V ALKALINE battery. (Burton Security recommend the Duracell brand).
- The batteries are located in compartment located on the underside of the keypad. Remove the battery compartment cover and carefully take out the battery.
- Unclip the wire and replace the battery. Take care when changing batteries to ensure that the battery cables don't become damaged.

Installation Guidelines for Freestanding Safes



When fixing your safe, it is important that it is fitted against a solid wall or concrete floor. Follow our guide below and for more information and guidance visit our website.